

RODAJA NEUMÁTICA, SEMI-NEUMÁTICA Y RELLENA



67 Series casters are made from cold rolled steel and feature double ball swivel raceways. 4 different shock absorbing wheels types provide the maximum cushion ride available; each wheel has unique characteristics and advantages to consider. A matching rigid caster (68 Series) and a total-locking (DT Series) are also available.

- **Pneumatic:** Air filled inner-tube and tire mounted on a heavy-duty metal rim; offer the best cushion ride and traction available, but are vulnerable to going flat. Available in black and non-marking gray.
- **Foam Filled Pneumatic:** Kenda brand foam filled pneumatic tire cannot go flat.
- **Ever-Roll™:** Solid micro-cellular polyurethane foam tire mounted on a heavy-duty metal rim; offers the same advantages as a pneumatic tire without worrying about air leaks! Black tread is non-marking. Not recommended for wet applications / environments. May develop a flat spot if parked with a load.
- **Eco-Rubber™:** Environmentally friendly recycled solid rubber wheel mounted on a plastic core, offers a cushioned ride and holds more weight than the other wheel options; it can however mark floors. Will not generate flat spot if parked with a load.

Applications include: various carts, platform trucks and equipment used in industrial, commercial, institutional and outdoor environments where a cushioned ride and the ability to roll over uneven floors and debris is a must. Offers good floor protection and quite rolling operation. Not meant for highway use.

TRY DuraQuick™ Shipping
Expedite 24Hr.
Expedited Factory Drop Ship Service - On In Stock Parts.

Top Plate Specifications

Plate Code	Overall Size	Bolt Hole Pattern	Mounting Bolt Size
17	4 x 4-1/2	2-5/8 x 3-5/8 slotted to 3 x 3	3/8
19	4-1/2 x 6-1/4	2-7/16 x 4-15/16 slotted to 3-3/8 x 5-1/4	3/8



Raceway Seals (L)

Options



Top Lock Brake (T)
(8" & 10" Swivels only)



Cam-Lock Brake (C)
(8", 10" & 12" Swivels)
(8" & 10" Rigid)



4-Position Lock (P)



4-Position Lock
Bolt on. Part# 4PSL27



4-Position Lock
Bolt on. Part# 4PFL27



DT Series Total-lock
Available in 6" Pneumatic &
8" Eco-Rubber (page 53)

Wheel Diameter	Tread Width	Wheel Type	Swivel Caster Part #'s		Rigid Caster Part #'s		Tire Color & Rim Finishing	Weight Cap	Overall Height	Swivel Radius
			Replace ** w/ fastening code, ## w/ bearing Code				Roller Bearings 38, 40			
6	2	Pneumatic 4-PLY		67FP60JB60**YY			Black on Zinc	150	7-1/2	4-9/16
8	2-1/2	Eco-Rubber™		67SN80UC##17YY		68SN80UC##17YY	Black on Gray	450	9-3/4	6-1/2
	2-3/4	Ever-Roll™	67ER80BC38**YY	67ER80BC##**YY	68ER80BC3817YY	68ER80BC##**YY	Black on Zinc	250		
	2-1/4	Pneumatic 4-PLY	67FP5B2C##**YY	67FP5B2C##**YY	67FP5B2C##**YY	67FP5B2C##**YY	Black on Zinc			
	3	Pneumatic 4-PLY	67FP8A4C38**YY	67FP8A4C##**YY	68FP8A4C38**YY	68FP8A4C##**YY	Black on Zinc			
		Pneumatic 4-PLY	67FP8A4Y38**YY	67FP8A4Y##**YY	68FP8A4Y38**YY	68FP8A4Y##**YY	Gray on Zinc			
Foam Fill Pneumatic		67FF8H4C38**YY	67FF8H4C##**YY	68FF8H4C38**YY	68FF8H4C##**YY	Black on Zinc				
10	2-3/4	Eco-Rubber™		67SN10UC##**YY		68SN10UC##**YY	Black on Gray	550	12-3/16	7-1/4
	3	Ever-Roll™	67ER10BC40**YY	67ER10BC##**YY	68ER10BC40**YY	68ER10BC##**YY	Black on Zinc	280		
	3-1/2	Pneumatic 4-PLY	67FP0D4C40**YY	67FP0D4C##**YY	68FP0D4C40**YY	68FP0D4C##**YY	Black on Zinc	350		
		Pneumatic 4-PLY	67FP0D4Y40**YY	67FP0D4Y##**YY	68FP0D4Y40**YY	68FP0D4Y##**YY	Gray on Zinc			
		Foam Fill Pneumatic	67FF0I4C40**YY	67FF0I4C##**YY	68FF0I4C40**YY	68FF0I4C##**YY	Black on Zinc			
		Pneumatic 6-PLY	67FP0E6C40**YY	67FP0E6C##**YY	68FP0E6C40**YY	68FP0E6C##**YY	Black on Zinc			
12	3	Eco-Rubber™		67SN12UC##**YY		68SN12UC##**YY	Black on Gray	850	15-3/4	7-3/4
	3-1/2	Pneumatic 4-PLY		67FP2D4T##**YY		68FP2D4T##**YY	Black on Zinc	460		
		Pneumatic 6-PLY	67EP2E6T40**YY	67EP2E6T##**YY	68EP2E6T40**YY	68EP2E6T##**YY	Black on Zinc	500		