

# RUEDA NEUMÁTICA CON FOAM DE RELLENO



- Kenda brand tire filled with microcelular polyurethane foam; offering the same advantages as Pneumatic wheels, but cannot go flat.
- Tires are mounted on either centered or offset rims/hubs. Centered rims for mounting in casters & equipment and offset rims for use on hand trucks & portable equipment. Rims are made out of high quality heavy duty steel, offering exceptional reliability.
- Offers the maximum cushion ride available, easily rolling over debris and small obstacles.
- Great for both indoor and outdoor use.
- Provides good floor protection and quiet rolling operation.
- Standard sizes and designs are listed; however custom wheels are available upon request, please inquire.

Tire Spec & Approx. Diameter	Tread Pattern	Ply Rating	Hub Length	Hub Design	Hub Type	Load Cap.	Color	Part Number	Replace ** with desired bearing code.			
									Plain Bore	Roller Bearings	Ball Bearings	Precision BB.
280-4 (8")	H	4	3-3/16	Centered	3-PC	250	Black/Zinc	FF8H4C**	95	38	51,52,53	P1,P2, P3
280-4 (8")	H	4	2-1/4	Offset	3-PC	250	Black/Zinc	FF8H4O**	95		51,52,53	P1,P2, P3
350-4 (10")	I	4	4	Centered	3-PC	350	Black/Zinc	FF0I4C**	95	40	51,52,53	P1,P2, P3
350-4 (10")	I	4	2-1/4	Offset	3-PC	350	Black/Zinc	FF0I4O**	95		51,52,53	P1,P2, P3

Bore & Bearing Sizes									
Bearing Code:	38	40	51	52	53	P1	P2	P3	95
Bearing Type:	Roller Bearings		Ball Bearings			Prec. Ball Bearings			Plain Bore
Inner Diameter	3/4	3/4	1/2	5/8	3/4	1/2	5/8	3/4	1-3/8

## Tread Pattern

8"

10"



H



I