

RUEDA DE HULE EN NYLON

NEW!



- Rubber tread vulcanized to a specially designed Nylon core.
- Special structure of core designed to create load and impact capacities equivalent to rubber on cast iron wheels.
- Rust-free; suitable for wash down, high humidity and outdoor environments.
- Offers shock absorbing cushioned ride, rolls over debris, offers floor protection & quiet rolling operation.
- Precision ball bearing available for improved mobility.
- Durometer: 80 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision Ball Bearings	Delrin Bearings
4	2	2-3/16	400	NR40JB**	84	02, 04, 05, 09, 92	60	56,57,11,12
5	2	2-3/16	450	NR50JB**	84	02, 04, 05, 09, 92	60	56,57,11,12
6	2	2-3/16	550	NR60JB**	84	02, 04, 05, 09, 92	60	56,57,11,12
8	2	2-3/16	600	NR80JB**	84	02, 04, 05, 09, 92	60	56,57,11,12

Bore & Bearing Sizes											
Bearing/Bore Code	02	04	05	09	11	12	56	57	60	84	92
Bearing / Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1-3/16	1/2