

The image displays two perspectives of a heavy-duty castor wheel. The left view is a side profile, showing a grey plastic housing, a dark grey wheel with a white inner ring, and a silver metal mounting plate. The right view is a front-facing perspective, highlighting a red plastic lever on the side of the housing, which is used to lock the wheel in place.

- Modern attractive design, injection molded from reinforced nylon polymer composite.
- Strong, lightweight, corrosion & chemical resistant.
- Sealed precision bearings in raceway & wheel.
- Variety of non-marking Thermo-Pro™ & Poly-Pro™ wheels.
- Variety of fastenings available in zinc plated and stainless steel.
- Total-lock brake simultaneously locks both the swivel & wheel.
- *Directional lock option secures swivel raceway in trailing position at 180°, while leaving the wheel to roll freely; offers assistance in rolling equipment in a straight line.



TRY **DuraQuick**™
Shipping
Expedite 24Hr.
Expedited Factory Drop Ship Service - On In Stock Parts.

<i>Fastening Options</i> (Replace ** in part number with desired plate or stem code)						
Plate Code	Overall Size		Bolt Hole Pattern		Mounting Bolt Size	
06	2-3/8 x 3-5/8		1-3/4 x 2-7/8 slotted to 3		5/16	
Order modular stems installed with stem code -or uninstalled by part#				Permanently attached stems		
Stem Code	Size	Stem Type	Modular Stem Part#	Stem Code	Size	Stem Type
ZZ	1/2"	Hollow kingpin - No fastening		67	1/2-13 x 1	Threaded
41	.865 x 2-1/4	Octagon w/Grip Ring	S7STO41	68	1/2-13 x 1-1/2	Threaded
51	3/4 x 2	Square w/ 3 cross drilled holes	S7STS51	70	1-1/2-13 x 2-3/4	Threaded
57	3/4 x 2	Round w/ 3 cross drilled holes	S7STR57	71	.720 - .851	Expandable Adapter
91	7/16 x 1-3/8	Grip Ring	S7STG91	72	.852 - .927	Expandable Adapter
95	.864 x 2-3/16	Grip Ring	S7STG95	73	.928 - 1.029	Expandable Adapter
S1	1/2-13 X 4	Threaded	S7STTS1	74	1.030 - 1.140	Expandable Adapter
S2	5/8-11 x 4	Threaded	S7STTS2	75	1.360 - 1.425	Expandable Adapter
S3	3/4 -10 x 6	Threaded	S7STTS3	76	1.426 - 1.589	Expandable Adapter
				77	1.790 - 1.850	Expandable Adapter

